Material Safety Data Sheet Omni Specialty Packaging For Compliance with OSHA 29 CFR 1910.1200 and ANSI Z400.1-1998

1. Product and Company Identification					
Product Name	MSDS Code Number				
PARTS MASTER AW HYDRAULIC OILS ALL GRADES					
Trade Name & Synonyms	Date of Last Revision 1/15/2007				
Chemical Name	Manufacturer Omni Specialty Packaging				
C.A.S. Number	Address 10399 Hwy. 1 Shreveport La. 71115				
Grades or Minor Variant Identities	Information Telephone Number				
	(318) 524-1100				
	Foreign Emergency Telephone Number				
Product Use (for Canada)	Emergency Telephone Number (318) 524-1100				

2. Composition/Information on Ingredients					
Hazardous Components	C.A.S Number	Exposure Limits Oil Mist	%		
Heavy Hydrotreated Naphthenic Distillates (Petroleum)	64742-52-5	5MG/m3	0-100		
Highly-Refined Petroleum Lubricant Oils	Mixture	5MG/M3	65-100		
Severly Hydrotreated Heavy Naphthenic Petroleum Oil	Mixture	5MG/M3	0-70		
Additive Mixture	N/A	5MG/M3	0-5		
OSHA Regulatory Status 29 CFR 1910.1200.					

	3. Hazards Ide	entification			
Emergency C	Dverview				
This produc	t is considered not hazardous under 29 CFR 1910.1200 (Hazard	Communication).			
Routes of Exposure	Signs and Symptoms	Single, Repeated, or Lifetime Exposures	Severity (Mild, Moderate, Severe)	Acute and Chronic Health Effect(s)	Target Organ(s)
Eye	Eye contact may result in slight irritation and redness.				
Skin	Minimally irritating upon direct contact.	May cause irritation/dermatitis.			
Inhalation	Low hazard at standard temperatures and pressures. Inhalation of oil mist or fumes can cause irritation of the nose, throat and upper respiratory tract				
Ingestion	Do not ingest. May cause nausea, vomiting/diarrhea.				
Other	On rare occasions, prolonged and repeated exposure to oil mist poses a risk of pulmonary disease such as chronic lung inflammation. This condition is usually asymptomatic as a result of repeated small aspirations.				
Medical Cond	litions Aggravated by Exposure		•	•	•
Personnel w	vith pre-existing skin disorders should avoid contact with this pro	duct.			

	4. First Aid Measures		
Routes of Exposure	First Aid Instructions	Immediate Medical Attention	Delayed
Eye	Flush with large amount of water for 15 minutes. Get medical attention if eye irritation develops or persists.	If material is hot, treat for thermal burns and take victim to the hospital immediately.	
Skin	Wash with soap and water. Remove contaminated clothes and wash before reuse. Get medical attention if skin discolor develops.		
Inhalation	This material is not expected to present an inhalation exposure at ambient conditions		
Ingestion	Do not induce vomiting. Get immediate medical attention or advice.		
Other	Not available		
Note to Physicians (Tr	eatment, Testing, and Monitoring)		

Not available

5. Fire Fighting Measures									
Flashpoint Method:	۴	Flammable (Explosive) Limits in Air LEL UEL			Autoignition Temperature	۴		Hazard Ra	iting
COC Min.	310	Not determine	ed	Not determined	(> 353 °C)	667		Health	0
Flame Propagation (for solids)	or Burnir	ng Rate	Proper Intensi	ties Contributing to Fire ty	Flammability Classification			Fire Reactivity PPE	1 0 B
Not Available	e Not Determined		Not Avaliable			PPE	В		
Extinguishing Media Extinguishing Media to Avoid					!	Reactions to Extinguish	ning Media		
Water fog, foam, CO ₂ , dry chemical Not Available					1	Not Available			
Protection and Procedures for Firefighters									
Wear positive pressure self-contained breathing apparatus (SCUBA). Use water to cool containers exposed to flames. Structural firefighters' protective clothing will only provide limited protection.									

Unusual Fire and Explosion Hazards

Mist or sprays may be flammable below the product normal flash point.

6. Accidental Release Measures

Spill/Leak Clean-up Procedures and Equipment

Observing health hazards described above, ventilate area. Dike to contain spill. Pick up free liquid for recycle and/or disposal. Residual liquid and/or solid can be absorbed on inert material. Keep from sewers and natural water.

Evacuation Procedures

Large spill

* Consider initial downwind evacuate for at least 300 meters (1000 feet). Fire

* If tank, rail car or tank car is involved in a fire, isolate for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.

Special Instructions

When using this material, do not eat, drink, or smoke. Wash thoroughly after handling. Keep away from animals and children.

Reporting Requirements

Spills that enter a water body must be reported immediately to the USEPA's National Response Center at (800)546-2972. Check with your local and state regulators regarding their reporting requirements.

7. Handling and Storage

Handling Practices and Warnings

Do not pressure, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode. See NFPA 30 and OSHA 1910.106 – flammable and combustible liquids.

Storage Practices and Warnings

Store away from heat, sparks, open flame, or strong oxidizing agents in closed and properly labeled containers. Empty containers retain product residue (liquid, and/or vapor) and can be dangerous.

8. Exposure Control/Personal Protection					
Other Engineering controls	Ventilation				
N/A	Additional area ventilation or local exhaust may be required to main	tain air concentrations below recommended limits.			
Routes of Entry:	Personal Protective Equipment (PPE) for Normal Use:	PPE for Emergencies			
Eye/Face	Safety glasses or face shield where splashing is possible.	Full face shield			
Skin	As needed to prevent repeated skin contact. Solvent resistant gloves should be used if needed.				
Inhalation	Not normally needed.	Respirator			

	9. Physical and Cl	nemical Prop	perties
Appearance			Odor
Amber Liquid			Petroleum odor
Normal Physical State:		Boiling Point	>500 ° F
X Liquid	Gas	Melting Point	N/A ° F
Solid	(Other)	Freezing Point	<-21 ° C
Specific Gravity or Density $(H_2 0 = 1)$	Solubility in Water		pH
0.87	Negligible		N/A
Vapor Pressure (mm Hg.)	Vapor Density (AIR = 1)		Evaporation Rate (Butyl Acetate = 1)
N/A	Not Determined		N/A
Other			
N/A			

10. Stability and Reactivity						
Incompatibility (Materials to Avoid)						
Open flame, and strong oxidizing agents.						
Hazardous Products Produced During Decomposition						
Decomposition and combustion products may include hydrogen sulfide, al calcium and zinc; aldehydes, carbon monoxide and carbon dioxide.	kyl mercaptans, sulfides, oxides or sulfur, oxides of : phosphorous,					
Hazardous Polymerization? May Occur X Will Not Occur Conditions to Avoid						
Stability? X Stable Unstable	Conditions to Avoid Sources of ignition					

11	Toxic	ologic	al Infor	mation
	IUNIC	UUUUU		παιισπ

Toxicity Data, Epidemiology Studies, Carcinogenicity, Neurological Effects, Genetic Effects, Reproductive Effects, or Structure Activity Data

Acute Toxicity: Test on similar materials show a low order of acute oral and dermal toxicity.

Acute Oral Effects: Test on similar materials indicates low order of acute toxicity.

Acute Inhalation Effects: Low acute toxicity expected on inhalation.

Skin Effects: Practically non-toxic if absorbed. Other similar highly refined products have not shown skin tumors in mouse skin painting studies. **Eye Irritation**: Minimal irritation on contact. Eye irritation slightly or practically non-irritating base on similar products.

Carcinogenicity: **Skin**: Not considered a potential carcinogen base on IP346 DMSO of less than 3.0 wt%

Genotoxicity: This product is considered non-mutagenic and has negative potential for tumor development based on from Modified Ames Assay, with Mutagenic Index of less than 1.0.

12. Ecological Information

Toxicity, Environmental Fate, Physical/Chemical Data, or Other Data Supporting Environmental Hazard Statements

If applied to leaves, this product may kill grasses and small plants by interfering with transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress to birds and mammals through ingestion during pelage grooming.

13. Disposal Considerations

Regulations

Dispose in accordance with all local, state, and federal regulations. Keep this product out of sewers and waterways.

Note: State or local requirements may differ from federal regulations. Processing or using this product may make the information here inappropriate. Waste generators are responsible for waste classification, transport, and disposal.

14. Transport Information

Regulated	for shipping?			Proper Shipping Name	Packing Group
	Yes	Х	No	N/A	N/A
	es in quantity, p ange product c		shipment	Hazard Class	Identification Number
	Yes	х	No	N/A	N/A
Other					
N/A					

15. Regulatory Information
Federal Regulations (OSHA, TSCA, CERCLA, FIFRA, EPCRA, CAA, CWA, SDWA, CPSA, DEA, FDA/USDA, etc.)
State Regulations
U.S. Federal Regulatory Information:
CERCLA/SARA 302/303/304 Categories: Extremely Hazardous Substances No (40 CFR 355 Appendix A) 311/312 Categories: Immediate (Acute) Health Effects No (40 CFR 370) Delayed (Chronic) Health Effects No Fire Hazard No
Sudden Release of Pressure Hazard No Reactivity Hazard No 313 Categories: Toxic Chemicals (40 CFR 372) No Clean Air Act: Hazardous Air Pollutants (HAPS) No Clean Water Act: If spilled into navigable waters it is reportable to National Response Center, 800-424-8802 (40 CFR 116; 401.15) Reportable Quantity = Oil Sheen present on navigable water surface OSHA (29 CFR 1910): This product is not hazardous under Hazard Communication Standard 29 CFR 1910.1200 RCRA (40 CFR 261.133) This product are listed on the EPA/TSCA inventory of chemicals. CAS No. 64742-52-5 CAS No. 64742-52-5
State Regulations: California Prop 65 No Proposition 65 chemicals exist in this product, no labeling required. Florida No listed ingredients are present Massachusetts RTK No listed ingredients are present Minnesota RTK No listed ingredients are present New Jersey RTK Lists petroleum oil, but this product does not contain hazardous ingredients. Pennsylvania RTK Lists petroleum oil, but this product does not contain hazardous ingredients greater than 3%. Illinois DOL TSL No listed ingredients are present
Other Regulations: WHMIS (Canada) Not listed on the Canadian Controlled Product Ingredient Disclosure and is compliant with Controlled Products Regulation CONEG Metals: Since cadmium, chromium, lead and mercury are not detectable and it does not exceed 100 ppm total in this product, it is compliant with CONEG Metals: This product is not known to be a dangerous good internationally. No known R-Phrases or S-Phrases Hazard Label None Danger Symbol None Danger Symbol None
International Regulations
N/A
Other Not all ingredients will be present in some finished products.

16. Other Information

Label Text, Hazard Rating System, Key Legend, or Other

Abbreviations

ACGIH(American Conference of Governmental Industrial Hygienists); ANSI(American National Standards Institute); CAS(Chemical Abstract Service); CERCLA(Comprehensive Environmental Response, Compensation, & Liability Act); CFR(Code of Federal Regulations); CHIP (Chemicals Hazard Information & Packaging for Supply); CONCAWE (European Organization for Environment, Health & Safety); CPR(Controlled Products Regulations); DOL (Department of Labor); EED(European Economic Community Directives); EINECS (European Inventory of Existing Commercial Chemical Substances); EL50 (Effective loading rate required to immobilize 50% invertebrate species); ELINCS(European List of New Chemical Substances); EPA (Environmental Protection Agency); EPCRA(Emergency Planning & Community Right-To-Know Act of 1986); EU(European Union); FDA(Food & Drug Administration-USA); GHS (Global Harmonization System); HCS (Hazard Communication Standard); IARC(International Agency for Research on Cancer); ILO(International Labor Organization); CDS(Lethal Concentration 50% test organisms); LD50(Lethal Dose 50% test organisms); LVP-VOC(Low Vapor Pressure Volatile Organic Compound); MSDS(Material Safety Data Sheet); MSHA(Mine Safety & Health Administration); NIOSH(National Institute of Occupational Safety & Health);NTP(National Toxicology Program); OSHA(Occupational Safety & Health Administration); RFPhrases(EU Risk Phrases; S-Phrases (EU Safety Phrases); SARA(Superfund Amendments & Reauthorization Act); TSCA (Toxic Substances Control Act); TSL (Toxic Substance List); TLV(Threshold Limit Value); WHMIS(Workplace Hazardous Materials Information System) canada); IrL50 (Inhibitory loading rate required to reduce algal growth rate by 50%; IbL50 (Inhibitory loading rate required to reduce area under growth curve or biomass by 50%); ppm (parts per million); mg/m3 (milligrams per cubic meter); N(no); Y (yes)

NFPA Hazard Rating	– Health	0 Slight	
	-Fire	1 Slight	
	Reactivity	0 Least	
Prepared By:	Juan Parker	Phone:	(318)524-1100

This MSDS complies with OSHA Hazard Communication Standard (HCS) 29 CFR 1910.1200 and conforms to ANSI Z 400.1 16-Section Format.

Disclaimer: Omni Specialty Packaging believes this information is accurate but not all-inclusive in all circumstances. It is the responsibility of the user to determine suitability of the material for their purposes. No warranty, expressed or implied, is given.

NOTE: OSHA's Hazard Communication Standard (29 CFR 1910.1200) does not require the information requested in Sections 11, 12, 13, 4, 15, and 16 for MSDSs. If your company chooses not to fill in these sections, you may wish to enter something (like N/R for "not regulated" or N/A for "not applicable") to indicate that the field is purposely being left blank.