



- Stops roof leaks
- Use for repair or new construction
- Use in wet or dry conditions
- Fiber reinforced
- Thick trowel grade

WHAT IS IT? Gardner® WET-R-Dri™ Roof Cement is an all weather, asphalt based patching compound designed to repair cracks, seams and holes in roofing materials. It also works great in new construction and in setting flashings, drip edges and roofing material edges.

WHAT IT DOES: It seals damaged areas and gives a layer of waterproof protection.

WHERE TO USE: On roofs around skylights, vents, exhaust pipes, chimneys, valleys, and in the construction or repair of flashings, roll roofing and shingles. Also excellent for use as a heavy duty below grade and underground water-proofer, and damp-proofer.

WHAT IS NEEDED TO COMPLETE THE JOB? Caulk gun, trowel or putty knife and gloves.

PREP THE AREA: Surfaces must be clean and free of surface rust and loose material.

HOW TO APPLY: Apply with a caulk gun. A trowel or putty knife may be used to blend cement to surface.

HOW MUCH DO I NEED? Provides approximately 25 lineal feet of 1/4" bead.

DO's and DON'Ts: Do apply in exterior applications only. Do wear protective clothing. Don't apply to plastic, EPDM, Hypalon or similar type of synthetic rubber roof system. If there is a question on compatibility, test a small section first before application to entire surface area.

FOR BEST RESULTS: It is highly recommended to reinforce the repair with a strip of reinforcing fabric. Work material to an even consistency over and into the area to be repaired approximately 1/8" to 1/2" thick, two or three inches beyond the problem area. Embed fabric into the cement and cover with a second layer of cement. Form a feathered edge with cement where chimney's, vent pipes, and other projections meet the roof line. DO NOT APPLY DIRECT HEAT/FLAMES OR THIN. Apply when surface temperatures are between 50°F and 120°F. In colder weather (50°F and below), product should be stored in heated room (70°F to 80°F) at least 24 hours prior to application to promote ease of application. Product formulated to be used year round. Allow product to cure a minimum of 30-60 days prior to application of reflective coating.

PRECAUTIONS: Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that tube is secure and upright. Do not allow tube to tip as this may cause leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100°F. This manufacturer also disclaims liability for flat surface application where poor drainage or ponding water may prevail. Do not reuse empty containers. Do not use in drinking water or food systems.

HOW TO CLEAN-UP: Clean tools or spills with paint thinner or mineral spirits.

© 2007 Gardner Asphalt Corp.
Manufactured by: Gardner Asphalt Corp.,
P.O. Box 5449, Tampa, FL 33675

See MSDS for more info

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

| | |
|---|---------------------------|
| Weight Per Gallon, lbs. | 8.2-8.6 lbs. |
| Residue by Evaporation, % | 42 min. |
| Combustible Solvents | Petroleum Solvents |
| Consistency | Trowel |
| Cure Time (50% Relative Humidity, 70°F) | N/A |
| Full Cure (50% Relative Humidity, 70°F) | N/A |
| Application Temperatures | 50°-120°F |
| Flammability | 105°F |
| Clean-up Tools | Mineral Spirits, Kerosene |

Approx. Shipping Weights: (Note: All approx. weights include container.)

| | |
|---------------------------|----------|
| 10.1 fl. oz. tube (300mL) | 0.7 lbs. |
| 29 fl. oz. tube (946mL) | 2 lbs. |
| 1 qt. (946mL) | 2 lbs. |
| 1 gallon (3.8L) | 8.4 lbs. |
| 5 gallons (18.9L) | 42 lbs. |
| 55 gallons (208.2L) | 460 lbs. |

CAUTION: HARMFUL OR FATAL IF SWALLOWED Use with adequate ventilation. Keep out of reach of children.

For exterior use only. Contains petroleum based products. Keep away from heat, sparks and open flame. Use only with adequate ventilation. Eye and skin irritant. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid contact with skin and breathing vapor. If swallowed, do not induce vomiting. Call physician immediately. Seal container when not in use.

CALIF. PROP. 65 . CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

VOC - 200 g/L max. (1.66 lbs./gal.)

COMPLIANCE: SCAQMD RULE # 1168

| | |
|------------------|--------------------|
| ASPHALT | C.A.S.# 8052-42-4 |
| MINERAL SPIRITS | C.A.S.# 8052-41-3 |
| CELLULOSE FIBER | C.A.S.# 65996-61-4 |
| CALCIUM SILICATE | C.A.S.# 1344-95-2 |
| INORGANIC FILLER | C.A.S.# 1317-65-3 |

Product is asbestos free.

PATENT PENDING

WARRANTY AND DISCLAIMER:

For limited warranty and disclaimer information, contact the Gardner corporate office at www.gardnerasphalt.com.



Gardner Asphalt Corp. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardnerasphalt.com